




LOGGIA
industria vernici

TECHNICAL DATA SHEET

Revisione: 12 novembre 2014



Sharki

Texture decorative refinishing with sandblast effect.

General Characteristics

Composition: SHARKI is acrylic refinishing for interior decoration with satin sandblast effect. Its irregular texture creates designs similar to the signs the wind makes on the sand dunes. It is indicated for both, modern and classical environments.

Recommended usage: SHARKI is perfect for protection and decoration of internal walls of modern and antique prestigious buildings as villas, hotels, banks and offices.

Preparation

Surface preparation:



Before to apply SHARKI is necessary to prepare properly the surface with powder or pasty putties (as FLYSTUK); 12 hours after it's necessary to sand it well with sand paper (we recommend grain type P150). After sanding and cleaning of possible dirtiness and dust, apply 1 coat of acrylic fixative FISSACRYL tinned with water 1:1 up to 1:3. After 4-5 hours apply by roller 2 coats of UNIVERSAL PRIMER WHITE OR COLOURED in the same shade of decorative paint.



Product Application

Methods: Spalter 1x10cm o Brush 3x10cm: Product diluted at 5-10% with water.



6-8 hours after UNIVERSAL PRIMER application, proceed with application of SHARKI with cross brush movements. To obtain a surface with more sand and shades it is possible to apply second coat of SHARKI trying to fill the empty spaces. It is possible to have various effects of SHARKI as oblique or simply vertical applying the product in one direction only.

Temperature for application:	+5 ÷ +35	°C
Humidity for application:	< 85%	
Dry film thickness:	50 ÷ 100	mm per coat
Dry Touch:	1 ÷ 2	h
Recoatable after:	6 - 8	h
Completely Cured:	48	h
Cleaning tools:	by water	

Colouring



This product can be colored with Tinting systems L'ANGELO and L'ANGELO OX as well as UNIVERSAL TONERS to obtain customized shades.

It is appropriate to mix different batches of the same color in order to ensure color uniformity during application.

SHARKI exists a part of classic, in version GOLD, SILVER and DIAMOND, sandblast finishes with metallic nuances of gold, silver with glitter.

Technical Properties

Density:	1,45 ÷ 1,55	Kg/l
Viscosity:	5000-10000	cPs
pH:	6-7	
Weight Solids:	60%	
Coverage:	6-7	mq/l
Color:	Color Chart	
Gloss level:	Sandblust Gold – Silver - Glitter	
Pack Size:	0,75 - 4	l

Storage



Shelf-life: Not less than 2 years in original tightly closed cans away from direct sunlight and excessive heat.

The can should be resealed and stored tightly closed to prevent evaporation of the product and air entry. Store it upside down after use



Min storage temperature: +5°C

Max storage temperature: +30°C

Safety Precautions

For all information regarding product use and correct product disposal please refer to Safety Data Sheet.

Warnings

All information contained in this data sheet are based on our technical knowledge. However these indications could not have a value of guarantee for applicator considering that conditions of applying of product is out of our control. It is advisable make sure of suitability of the product making preliminary test.
